

Datasheet

OBC/LRT Deck Unit



Part of Sonardyne's Coastal Acoustic Product Range, the Type 7967 OBC/LRT Deck Unit is used to command and programme Sonardyne's range of TZ/OBC transponders and Lightweight Release Transponders (LRTs). It comprises of a deck unit and dunking transducer supplied with 10 m of cable.


The deck unit is used initially to program the acoustic identity of the transponder, test the transponder and, in the case of the LRT, load the release 'bit' prior to deployment. Once deployed, it can be used to measure ranges to the transponder and prior to sending a secure release command, relocate the transponder. The deck unit can also be controlled via RS232 enabling raw range data to be logged to a PC for processing.

Key features

- Supplied in rugged, portable case
- For use with Type 7815 TZ/OBC Transponders and Type 7986 Lightweight Release Transponders
- Enables transponders to be tested and programmed with thousands of unique identities prior to deployment
- Highly secure coding sequence prior to commanding LRTs to 'release'
- Powered by alkaline battery packs; supplied with 2 spare packs
- Easy to operate

Specifications

OBC/LRT Deck Unit



Feature	Type 7967
Operating frequency	HF (33–50 kHz)
Transmit source level (dB re 1 μ Pa @ 1 m)	185 dB
Receive sensitivity (dB re 1 μ Pa)	110 dB
Pulse length	2 ms
Timing resolution	16 ms
Transducer ports	1
Number of independent navigation channels	9
Dimensions (length x width x height)	360 x 270 x 155 mm (14.1 x 10.6 x 6.1")
Power supply	Alkaline Battery
Weight	5 kg

Ordering Information

Types	Description
7967-000-02	LRT Surface Control Unit
7967-036	Programming Lead
7967-002	Remote Transducer
7967-037	RS232 Interface Cable
7815-044	Alkaline Battery Pack

Specifications subject to change without notice – 03/2023

For further information, contact us at