


Datasheet

Nano OEM Transponder



The Wideband® Nano Transponder is specially designed for acoustic positioning of divers or small underwater vehicles. The small lightweight family of transponders allow for easy, unobtrusive attachment to a diver or vehicle.

Available in three variants: NFC, Cabled and OEM, there is a Nano Transponder for every use case.

All variants are depth rated to 500 m and have an acoustic source level and beam shape that is designed to operate over a 995°m slant range under normal conditions. Three months battery life means they are suitable for long term deployments, marker beacons and for vehicle recovery.

A 500 m pressure sensor optimises acoustic performance at long horizontal ranges by constraining the depth measurement, making the nano perfect for Towed vehicle, AUV and Diver tracking.

The Nano Transponder family operates in the Medium Frequency (MF) band and is compatible with Sonardyne's Mini-Ranger 2 6G® Wideband USBL system.

The NFC Nano Transponder features a unique connector-less design that is recharged and programmed via the Nano Docking Station. The NFC technology allows full configuration of the Nano whilst maintaining its rugged "strap on and go" form factor.

The Cabled Nano Transponder features an industry standard Subconn connector allowing the Nano to be permanently powered and can also be used in Responder mode.


For vehicle programs and integrators, the Nano OEM when paired with an OEM transducer provides all of the functionality of the housed transponders, in a form factor that can be mounted in any system.

Key Features

- Miniature size for fitting on divers and small ROVs
- Configurable form factor
- Depth rated to 500 m
- Powerful acoustic transmission level
- Medium Frequency operation
- Compatible with Sonardyne Ranger 2 USBL systems
- Configuration using the Nano Docking Station wireless communications
- Battery disconnect storage mode
- Integrated pressure sensor for depth aiding
- >300 independent acoustic addresses
- Wide dc voltage input range
- Gainless for ease of use
- Common form factor with AvTrak 6 Nano so common transponders can be used across a fleet

Specifications

Nano OEM Transponder



Feature		Type 8262 Nano OEM
Operating Range		995 m ¹
Transducer Depth Rating		500 m
Operating Frequency		MF (19–34 kHz)
Transducer Beam Shape		Omni-directional ±130°
Source Level (re 1 µPa @ 1 m)		184/175 dB
Range Precision		Better than 15 mm
Communication Interface		RS232, 3V3 TTL
Depth Sensor		50 bar abs +/-0.7% FS
Power Supply ²		12–28 V dc
Power Consumption	Wideband Listening (Battery)	5 mW
	Wideband Listening (External Power) ³	20 mW (including trickle charge)
	Battery Charging	60 mW to 2.5 W (depending on battery charge state)
	Peak (During Transmission)	<30 W SMS, <20 W Modem
Battery Life	Quiescent Listening	>90 days
	1 Sec Ping Rate	>12 hours
Battery Charge Time		12 hours
External Connections		Molex Microfit
Transducer Wire Length ⁴		150 mm (6")
Operating Temperature ⁵		-10 to 45°C
Storage Temperature ⁶		-20 to 55°C
Dimensions	Transducer (Length x Diameter)	72 x 49 mm
	PCB Board Assembly (Length x Width x Height)	95 x 43 x 42.5 mm
	Hole Centres (M2 clearance – Length x Width)	71.5 x 35 mm
Weights	PCB in Air	138 g PCB + 12 g cable
	Transducer in Air/Water (Estimated)	200/150 g

¹ When used with Micro-Ranger/range limited Ranger 2 systems.

² Noise on the external dc supply may have an effect on the acoustic performance of the instrument.

³ Includes top-up charging of the li-ion battery, which could be disabled, or managed intelligently for better efficiency.

⁴ It is possible to increase the transducer wire length if required; contact Sonardyne for more information.

⁵ The battery will not charge above 45°C or below 0°C.

⁶ To maximise battery life, the instrument should not be stored above 30°C.