

---

<b>Bulletin No.</b>	TB-12-007	<b>Issue Date:</b>	24/07/12
<b>Issue/Revision:</b>	1	<b>No. of Pages:</b>	1
<b>Prepared By:</b>	K.WEEDON	<b>Signature/Date:</b>	<i>K.A. Weedon</i>
<b>Approved By:</b>	D.NEWBOROUGH	<b>Signature/Date:</b>	<i>D. Newborough</i> 20 27/07/12

---

## Subject: Change to WMT Charger Specification

### Summary:

Changes were made to the WMT (8190) at the beginning of 2012 to improve the reliability of the internal power regulation. This required the minimum operating voltage to be increased from 18V to 20V. When this change was made; the WMT charger kit (650-0043) was also updated to use a 24VDC PSU.

- The new 24VDC WMT charger PSU (8190-006-01) will work with all WMTs (8190).
- The old 18VDC WMT charger PSU (8063-005-01) will not work with a WMT manufactured from the beginning of 2012. All new WMTs are shipped with the new 24V charger PSU, which will work with all WMTs.

### Solution:

We will be despatching the new replacement 24VDC WMT charger PSU (8190-006-01) to all customers with a WMT. Upon receiving the new charger, please return the old 18VDC WMT charger PSU (8063-005-01) to your nearest regional office. This will ensure that the WMT will charge correct regardless of build date.

Please supply us with a delivery address for the new WMT charger by emailing [support@sonardyne.com](mailto:support@sonardyne.com). We will dispatch your new charger upon receipt of delivery address.

Should you require any further clarification please contact customer support on [support@sonardyne.com](mailto:support@sonardyne.com) or +44 1252 877600.

**END.**